

X-RAY TUBE CATHODE CUP STRUCTURE
FOR FOCAL SPOT DEFLECTION

This application is a Continuation-in-Part of U.S. Application Serial No. 09/989,864, filed November 20, 2001.

Background of the Invention

The present invention pertains to the vacuum tube arts, and in particular to an x-ray tube cathode cup structure for deflecting a focal spot of a beam of electrons. It finds particular application in conjunction with rotating anode x-ray tubes for CT scanners and will be described with particular reference thereto. However, it is to be appreciated that the present invention will also find application in the generation of radiation and in vacuum tubes for other applications.

Conventional x-ray tubes include a vacuum enclosure and a source of a beam of electrons in the form of a cathode. The cathode includes a heated filament which emits electrons. The impact of the electron beam on the anode causes a beam of x-radiation to be emitted from the x-ray tube, typically through a beryllium window. A trend toward shorter x-ray exposure times in radiography has placed an emphasis on having a greater intensity of radiation and hence higher electron currents. Increasing the intensity can cause overheating of the x-ray tube anode. An electrical bias voltage is applied to the beam of electrons in order to control, to some extent, the size of the focal spot.

One way to control the size of the focal spot of the electrons on the anode more closely is to mount the

cathode filament within a cathode focusing or support cup member. Such a system is shown in U.S. Patent No. 4,689,809. A cathode cup is split into two portions, surrounding the filament. The portions are biased equal to
5 or negative with respect to the filament. The biased cup reduces unwanted "wings," or diffused areas, appearing as part of the x-ray focal spot.

Other cathode cup and filament arrangements for controlling the size and shape of the electron focal spot on
10 the tube anode are discussed in U.S. Patent Nos. 4,685,118, 5,224,143, and 5,065,420.

To minimize the power requirements of the focussing system and to maintain accurate positioning of the filament relative to the deflectors, it is desirable to
15 mount both the deflectors and the filament to the same support. Cathode cups thus typically include a base or arm portion which supports the filament and a pair of deflectors. The deflectors are mechanically mounted to the base, but are electrically insulated from it. This is
20 achieved through the use of ceramic insulators which are brazed to both the base and the deflectors in the form of a sandwich. The ceramic insulators include central bores through which a bolt is received for maintaining alignment of the components during brazing. To avoid shorting, the
25 bolt is electrically isolated from the base. Such a cathode cup design is difficult to assemble, difficult to align, and is susceptible to shorting. This can occur if the material used to braze the ceramic insulator to the base or the deflector flows into the insulator bore that receives the
30 bolt. Shorting can also occur due to natural plating of the ceramic insulator with metal vapor from the filament.

The present invention provides a new and improved x-ray tube and method which overcomes the above-referenced problems and others.

In accordance with one aspect of the present invention, a cathode assembly is provided. The assembly includes a base. A filament is mounted to the base for delivering a stream of electrons. A deflector is carried by
5 the base for deflecting the electrons and/or focusing the electrons into a beam. An insulator electrically insulates the deflector from the base. The insulator defines a bore. A rod is connected with the deflector adjacent a first end of the rod. The rod is received within the insulator bore.

10 In accordance with another aspect of the present invention, an x ray tube is provided. The x-ray tube includes an envelope which encloses an evacuated chamber. A cathode assembly is disposed within the chamber for providing a source of electrons. The cathode assembly
15 includes a base supported in the envelope. A filament is mounted to the base for providing the electrons. A deflector is carried by the base for deflecting the electrons and/or focusing the electrons into a beam. An insulator electrically insulates the deflector from the
20 base. The insulator defines a bore. A rod is connected with the deflector adjacent a first end of the rod, the rod being received within the insulator bore. An anode is disposed within the chamber and positioned to be struck by the electrons and generate x-rays.

25 In accordance with another aspect of the present invention, a method of assembling a cathode assembly is provided. The method includes attaching at least one rod to at least one deflector and attaching a metal tube in an insulator to define a bore for receiving the rod. The
30 insulator is attached to a base. A filament assembly is attached to the base. The method further includes sliding the rod into the tube to mount the deflector to the base and attaching the rod to the tube.

One advantage of at least one embodiment of the
35 present invention is that a cathode cup is electrically isolated from a filament.

Another advantage of at least one embodiment of

the present invention is that deflectors of a cathode cup are readily aligned with a filament.

Another advantage of at least one embodiment of the present invention is that components of a cathode cup
5 are accurately aligned.

Another advantage of at least one embodiment of the present invention is that deposition of vaporized filament material on to insulators which space the deflectors from a base assembly is minimized by reducing the
10 line of sight between the filament and the insulators.

Still further advantages of the present invention will become apparent to those of ordinary skill in the art upon reading and understanding the following detailed description of the preferred embodiments.

15 Brief Description of the Drawings

The invention may take form in various components and arrangements of components, and in various steps and arrangements of steps. The drawings are only for purposes of illustrating a preferred embodiment and are not to be
20 construed as limiting the invention.

FIGURE 1 is a schematic sectional view of a rotating anode x-ray tube according to the present invention;

FIGURE 2 is a side view of a cathode assembly of
25 the x-ray tube of FIGURE 1;

FIGURE 3 is a front perspective view of the cathode assembly of FIGURE 2;

FIGURE 4 is a top view of the cathode assembly of
FIGURE 2;

FIGURE 5 is a sectional view of the cathode assembly through line B-B of FIGURE 4;

FIGURE 6 is an exploded perspective view of the cathode assembly of FIGURE 2;

FIGURE 7 is an enlarged perspective view of a
35 cathode assembly according to an alternative embodiment of the invention; and

FIGURE 8 is a sectional view of the cathode assembly of FIGURE 7.

Detailed Description of the Preferred Embodiments

With reference to FIGURE 1, a rotating anode x-ray tube 1 of the type used in medical diagnostic systems for providing a beam of x-ray radiation is shown. The tube includes an anode 10 which is rotatably mounted in an evacuated chamber 12, defined by an envelope or frame 14. A heated element cathode assembly 18 supplies and focuses an electron beam A. The cathode is biased, relative to the anode 10 such that the electron beam flows to the anode and strikes a target area 20 of the anode. A portion of the beam striking the target area is converted to x-rays B, which are emitted from the x-ray tube through a window 22 in the envelope. The cathode assembly includes a cathode cup or head 24, which is supported in the envelope by an arm 26 of the cathode assembly 18, which is connected at its other end to a central support structure 28.

The target 20 of the anode is connected to a shaft 40, which is supported by bearings 42 in a neck portion 46 of the evacuated envelope 14 and driven by an induction motor 48. The induction motor includes a stator 50, outside the envelope, which rotates a rotor 52 connected to the shaft relative to a stationary bearing housing 54. The anode is rotated at high speed during operation of the tube. It is to be appreciated that the invention is also applicable to stationary anode x-ray tubes, rotating cathode tubes, and other electrode vacuum tubes.

With reference now to FIGURES 2-6, the cathode head 24 includes a base 60, which may be integrally formed with the arm 26 or mounted thereto, for example, by brazing or welding, or by affixing the arm to the base with bolts 62 or other suitable attachment members threaded through holes 64 in the base (FIGURE 4). A filament assembly 66 is supported by the base. As shown in FIGURE 2, two insulative filament supports or posts 67, 67' are provided for

supporting respective ends of the filament. Alternatively, as shown in FIGURE 3, one of the insulative filament supports is omitted, and the filament is grounded through the base 60. The support or supports 67, 67' are received through corresponding bores 68, 68', which extend axially through the base such that an electron-emitting portion or tip 70 of the filament assembly is spaced from the base. The filament supports may be fixed in this position by brazing the filament supports 67, 67' to the respective bore or by other means, such as threading a threaded portion of the filament supports 67, 67' to corresponding threads in the respective bore. It will be appreciated that two or more filament assemblies may be used in place of the single filament assembly shown, if desired. The filament supports 67, 67' may be formed from ceramic, or other suitable insulative material. Preferably, each support has a tube 71, 71' of nickel and/or Kovar™ brazed into an interior bore thereof (not shown). In the case of the embodiment of FIGURE 3, the tube 71 is received through corresponding bore 68, and is preferably brazed directly thereto. Niobium shanks 73, 73' at ends of the tungsten filament are received through respective bores in the tubes 71 after the tubes have been mounted in the respective filament support or supports 67, 67' (FIGURE 5). When it is time to position the filament 66, the two niobium shanks at the ends of the filament are inserted into the respective tubes 71. A microscope is used to adjust the height of the filament tip 70. When the filament tip is correctly positioned relative to the base 60, the tubes 71, 71' are crimped around the respective shanks 73, 73' to maintain the position of the filament until welding takes place, for example, by laser welding the shanks to the tubes 71, 71'. Prior to welding, the tungsten filament is preferably annealed to grow the filament into a single crystal tungsten structure, for example, by flashing a high current through the filament in a hydrogen atmosphere.

The filament assembly 66 is connected by conductors 74

to a suitable power source 76 outside the envelope (FIGURE 3). Although a wire filament is illustrated, it is to be understood that other electron sources are also contemplated, including thin film filaments, and the like.

5 Deflectors 80, 82 are carried by the base 60 in a manner which electrically insulates the deflectors from the base. Two deflectors are shown in FIGURE 3, although a single deflector, or more than two deflectors, could alternatively be used. The deflectors are positioned in
10 close proximity to the filament tip 70 for deflecting and/or focussing the beam of electrons emitted by the filament. This allows the size and location of a focal spot 86 on the target (FIGURE 1) to be controlled and adjusted.

As shown in FIGURE 3, the deflectors 80, 82 are
15 generally mirror images of each other and are positioned on opposite sides of the filament tip 70. Each deflector has an upper surface 90 and lower surface 92 (the terms "upper" and "lower" being used with reference to the orientation shown in FIGURE 3, the upper surface being closer to the
20 base 60). A side wall 94 of the deflector projects inwardly, towards the filament, in the region of the filament tip 70, thus providing a relatively narrow gap 96 between respective projecting portions 97, 97' of the two deflectors in the region of the filament tip.

25 The deflectors 80, 82 may be formed from molybdenum, or other suitable temperature resistant, electrically conductive material. The base 60 may also be formed from molybdenum, or may be formed from less expensive, easier to machine materials, such as nickel,
30 since it does not need to withstand as high temperatures as the deflector.

With particular reference to FIGURES 4 and 6, the deflectors 80, 82 are spaced and insulated from the base by insulators 98, 100, 98', 100'. As shown in FIGURE 4, four
35 insulators are employed, two for each deflector. For stability, it is preferable to use two (or more) insulators for each deflector, spaced longitudinally from each other,

although it will be appreciated that a single insulator may be used. For ease of reference, the cathode will be described with reference to two deflectors, each having two insulators. As shown in phantom in FIGURE 4, the filament tip 70 extends between the forward and rear shanks 73, 73' along a line which is generally coincident with the longitudinal axis of the base 60 and perpendicular to a line B-B between the forward pair of insulators 98, 100 and is equally spaced from each insulator 98, 100, 98', 100' at its closest point thereto.

As best shown in FIGURES 5 and 6, each insulator 98, 100, 98', 100' comprises a cylindrical block 104, 105, each with a central axial bore 106. A first, lower portion 110 of each block 104, 105 is received within a correspondingly shaped cylindrical socket 112 in the deflector 80, 82. It will be understood that different shaped insulator blocks may be used, such as rectangular blocks and a corresponding shaped socket in the deflector provided. As will be appreciated, two sockets are formed in each deflector to receive corresponding insulator blocks, a total of four sockets in all. Each socket extends partway into the deflector, preferably, about half way.

The socket 112 has a slightly larger diameter than the corresponding block 104, 105, such that a gap 116 spaces the insulator from the deflector adjacent a cylindrical side 118 and preferably also a base 119 of the insulator block 104, 105. The gap 116 is preferably about 70-100 microns in width, such that a space is maintained between the insulator 104, 105, and the deflector 80, 82. This reduces the risk of shorting out. In service, insulators sometimes become coated with a plating layer formed by evaporation of filament material. Leaving a gap between the insulator and the deflector allows for a fairly thick layer of plating material to accumulate without resulting in shorting out.

A second upper (in FIGURE 6) portion 120 of each insulator block 104, 105 is received within a cylindrical passageway 122 in the base (four passageways are shown in

FIGURE 4). The passageway 122 is chamfered to create a smaller diameter portion 124 at the upper end thereof with a shoulder 126 for providing an upper stop for the insulator block 104, 105.

5 The insulator blocks 104, 105 are formed from an electrically insulating material, such as alumina. For example, 94% purity or 99% purity alumina may be used, such as AD 94, AL 500, or equivalent purity. Al_2O_3 meeting ASTM Standard D2442 Type 4 is an exemplary insulating material.
10 For effective electrical insulation of the deflector from the base (and the filament), the insulators preferably provide a resistance of at least 720 giga-ohm.

 A pair of deflector rods 130, 130', 132, 132', formed from an electrically conductive material, such as
15 niobium, are mounted to each deflector 80, 82 (i.e., four rods in total) and are received through the corresponding bore 106 of the insulator blocks 104, 105. The deflector rods 130, 130', 132, 132' are electrically connected to a respective bias supply 134, 135 by suitable wiring 136
20 (FIGURE 3). One bias supply is preferably provided for each deflector. The rod is electrically insulated from the base 60 by the corresponding insulator block 104, 105 and by a gap 138 at the upper end portion 124 of the insulator passage 122.

25 The deflector rods 130, 130', 132, 132' provide an electrically conductive path to the respective deflector 80, 82 for biasing the deflector to an appropriate voltage for deflecting or focusing the electron beam. For example, as the two deflectors 80, 82 both become more negative,
30 relative to the filament, the size of the focal spot is reduced. When they become sufficiently negative, the electron beam is turned off. If one deflector is more negative than the other, the focal spot moves away from the more negative part. This latter result can be achieved by
35 biasing only one of the deflectors and having the other deflector at the same potential as the filament. Because of the close proximity of the deflectors to the filament, a

small bias is able to deflect or focus the beam. The two bias supplies 134, 135 may be computer controlled to permit automatic control of the width and positioning of the focal spot to a multiplicity of locations.

5 Each rod 130, 130', 132, 132' is preferably brazed to the deflector prior to insertion of the rod in the corresponding insulator block bore 106. As shown in FIGURE 6, each deflector has a depression 140, such as central hole machined in the base of each socket 112, and shaped to
10 receive one end 142 of the respective rod 130, 130', 132, 132'. To attach the rod to the deflector, the rod is positioned in the hole 140, together with a small piece of a suitable braze material, and the assembly heated to an appropriate temperature to braze the two components 130, 80
15 together.

 In an alternative embodiment, pairs of deflector rods 130, 130' and 132, 132', respectively, are connected at their ends 142 by a connecting portion (not shown) to form a generally U-shaped member. In this embodiment, the
20 depression 140 takes the form of a slot, shaped to receive the connecting member therein. The connecting portion is positioned in the slot 140, together with a small piece of a suitable braze material, and the assembly heated to an appropriate temperature to braze the two components
25 together. Other methods of attaching the rod 130, 132 to the deflector 80, 82 are also contemplated.

 Each of the insulator blocks 104, 105 preferably has a cylindrical tube 146, 147, 146', 147' mounted axially in the central bore 106 for receiving the corresponding rod.
30 Although only two tubes 146, 147 and two blocks are shown in the view of FIGURE 6, it will be appreciated that a tube is provided for each insulator block. Thus, for this embodiment, four tubes 146, 147, 146', 147' are employed, as shown in FIGURE 4. Each passageway, insulator block bore,
35 and corresponding tube and rod are preferably concentrically arranged, as shown in FIGURE 4. As shown in FIGURE 5, the tube 146, 147 has an upper end which extends beyond the

upper end of the insulator block, when installed, and is preferably of sufficient length to extend above the base 60 when the insulator block 104, 105 is located in the base. At a lower end, the tube 146, 147, when installed, is preferably flush with the base 119 of the insulator block, or may be slightly set back within the block.

The tube 146, 147 has an axially extending bore 148 therethrough with an internal diameter which is only slightly larger than the diameter of the corresponding rod 130, 132 so that the rod fits snugly in the tube bore. For example, the rod 130, 132 may have an OD of 0.100 cm + 0.000/-0.018 and the corresponding tube 146, 147 an ID of 0.104 cm + 0.025/-0.000. The tube is preferably formed from a material which is readily welded to the rod, for example, by laser welding. Exemplary materials for forming the tube include nickel and Kovar™. The tube 146, 147 is attached to the insulator block 104, 105 by brazing the two parts together, for example, by heating the tube and block with a suitable braze material between them. The quantity of braze material used should be sufficient to attach the parts firmly, without overflowing significantly at ends of the insulator block. This step is preferably carried out prior to inserting the insulator block into the base passageway 122.

The insulator blocks 104, 105 for the deflectors and the insulative support(s) 67, 67' for the filament assembly 66 (or tube 71, in the case of the embodiment of FIGURES 3 and 4) are brazed to the cup base 60 by heating the base and insulator, together with a suitable brazing material. The deflector insulator blocks 104, 105 and the insulative supports 67, 67' may be brazed into the base at the same time. However, in this embodiment, because the insulator blocks 104, 105 are inserted from the bottom of the base and the insulative support(s) 67, 67' for the filament are inserted from the top of the base, it may be preferable to braze first one set of insulators (either the filament or the deflector insulators) and then flip the base

over and braze the other set of insulators.

The brazing material for the insulator blocks 104, 105 is preferably positioned in the shelf region. The brazing material can be the same type as is used to attach
5 the tube to the insulator block and the rod to the deflector. However, since the brazing is preferably carried out in three separate steps (rod to deflector, tube to block, and block to base), the brazing material for each of the three joints can be a different material which is
10 compatible with the parts to be joined and heated to an appropriate temperature for the respective braze material to melt.

To provide a suitable surface for brazing, the insulator block preferably has a very thin surface coating
15 150 of a metallizing material, such as a molybdenum-manganese or tungsten-manganese composite material (shown exaggerated in the thickness in FIGURE 6). The coating may be deposited on the block by suitable deposition techniques to a thickness of about 5-20 microns. Preferably, the
20 metallizing layer extends over only a portion of the outer surface of the blocks, such as at the upper end of the block in the region where the braze material will be applied, to minimize risk of shorting between the base and the deflector.

The insulator tubes 146, 147 are welded or
25 otherwise attached to the rods 130, 132, for example, by laser welding. This step is preferably carried out after the insulators 104, 105 have been brazed into the base. This allows the deflectors to be properly aligned with the
30 filament. The length of the deflector rods 130, 132 is preferably selected such that, when the deflectors are correctly positioned, the rods are level with or protrude by a small amount from the upper ends of their respective tubes 146, 147.

35 To ensure alignment of the filament tip 70 with the deflectors, the insulative filament posts 67, 67' are preferably seated in the base 60 and the ends of the

filament 66 positioned (crimped, or crimped and welded) before inserting the deflector rods 130, 132 into the insulator tubes 146, 147. The rods are then inserted into their respective tubes. A gauge (not shown) of the appropriate thickness is then inserted between the deflector and the base to determine an appropriate gap 152 between the deflector and the base. The base and deflector are pushed towards each other (the rods sliding in their respective tubes) until the base and deflector contact the gauge.

Prior to laser or otherwise welding the insulator tubes 146, 147 to the deflector rods 130, 132, the respective insulator tubes and rods are optionally crimped together to hold the desired set position. The two deflectors 80, 82 are preferably positioned so that the filament tip 70 is approximately halfway between top and bottom surfaces of the deflector. This minimizes the risk of metallization of the insulator by material evaporating from the filament and avoids a "line of sight" being created in which material from the filament can travel in a straight line to the insulator. As can be seen from FIGURE 5, the deflectors are positioned such that material evaporating from the filament tip 70 will be inhibited by the projections 97, 97' from traveling directly towards the insulator blocks, the closest direct paths x and y to the insulators 98, 100 taking the material to the base 60, rather than to the insulator.

In an alternate embodiment, illustrated in FIGURES 7 and 8, a cathode assembly 216 is shown. The cathode assembly is similar to assembly 18 and includes a base 220, similar to base 60, with four bores 222, 222', 224, 224' for receiving deflector insulator blocks 226, 226', 228, 228'. The bores and insulator blocks are similar to those shown in FIGURES 2-6. However, in this embodiment, the bores are constructed for the insulator blocks to be mounted from an upper surface 230 of the base, rather than from the lower surface 232, as is the case in the embodiment of FIGURES 2-6. This allows the cathode filament support(s) 67, 67' (not

shown) and the insulator blocks 226, 226', 228, 228' to be mounted from the same side 230 of the base and facilitates brazing by allowing the cathode filament supports 67, 67' and insulator blocks 226, 226', 228, 228' to be readily brazed in the same operation.

As shown in FIGURE 8, the bores each have an tapered shoulder portion 240 between a widened upper portion 242 and a narrower lower portion 244 of the bore. The insulator blocks 226, 226', 228, 228' are shaped with a shoulder portion 246 between a widened upper portion 248 and a narrower lower portion 250 of the block. The lower portion of the block is received at its lower end by the corresponding deflector 80, 82. The shoulder portion 246 of the block sits on the bore shoulder portion 240. Prior to brazing, a small amount of brazing material is placed in the generally triangular space between the two shoulders 246, 240 for sealing the two components together when brazed. The shoulder portion 246 of the insulating block may be metallized prior to inserting the block into the bore to provide a good weld joint. An insulation gap 252 may be provided between the narrow portion 250 of the insulating block and the lower portion 244 of the bore. The gap ensures that even if a small portion of material evaporated from the filament tip enters the lower portion of the bore, it is deposited adjacent the surface 232, and the insulative barrier between the deflector and the base is not impaired. A similar arrangement (not shown) is used for brazing the filament support(s) 67, 67' into the respective bores 68, 68' to that described previously. Assembly of the cathode assembly 216 is otherwise the same as for the embodiment of FIGURES 2-6.

Other components of the cathode assembly are analogous to those described for the embodiment of FIGURES 2-6 and are given the same numerals. As for the earlier embodiment, deflector rods 130, 132 are brazed to the deflectors 80, 82 with brazing material 260 (FIGURE 8). The rods are then positioned in the respective tube bores 148 and, after

adjusting the height of the deflector, the tubes are crimped and welded or otherwise attached to the rods.

While in this embodiment, both the deflector insulator blocks and the filament supports are inserted from the top of the block, it is also contemplated that the base may be configured for inserting both the insulator blocks and filament supports from the bottom of the base.

A preferred method of assembling the cathode is thus as follows:

- 10 a) brazing the rods 130, 132 to the deflectors 80, 82,
- b) brazing the tubes 146, 147 to the insulator blocks 104, 105,
- c) brazing the insulator blocks 104, 105 (or 226, 228) and filament supports 67,67' (or tube 71) to the base 60,
- 15 d) setting the filament tip 70 height by positioning and fixing filament shanks 73, 73' into tubes 71, 71' in the insulative supports 67,67',
- e) setting the deflector height with a gauge and crimping the tubes 146, 147 to the rods 130, 132,
- 20 f) welding the tubes 146, 147 to the rods 130, 132.

As will be appreciated, step b) may alternatively be carried out before or concurrently with step a) and steps a), b), and/or c) may be carried out after step d).

Assembling the components stepwise, with three separate brazing steps a), b), c), and a welding step f), rather than brazing the insulator to the base and to the deflector in a single brazing operation, minimizes tolerance stackups due to improper alignment of the three components. The deflectors 80, 82 are easily aligned with respect to the filament tip 70, simply by sliding the rods 130, 132 up and down in their respective tubes 146, 147. Having two (or more) tubes which fit snugly to the corresponding rods and thus guide their movement ensures that the deflector remains parallel with the base as it is being positioned.

The invention has been described with reference to the preferred embodiment. Obviously, modifications and alterations will occur to others upon reading and understanding the preceding detailed description. It is
5 intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227